

3 AA BATTERIES

XPP-5422BA, XPP-5422GA

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

NIGHTSTICK®
Life Depends on Light

DUAL-LIGHT

240-lumen Dual-Light provides simultaneous **flashlight and floodlight** operation

IP67
DUST/WATER
PROOF

ATEX
ZONE 0
IECEx

CLASS I
DIV 1


XPP-5422GA

AVAILABLE IN MULTIPLE
COLORS
XPP-5422BA

240 LUMENS



Simultaneous **flashlight and floodlight** operation



Sharp focused flashlight beam



Durable polymer body is **impact & chemical resistant**



Large, textured buttons



1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT FLASHLIGHT

3 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5422BA, UPC 0 1739880807 1
- XPP-5422GA, UPC 0 1739880808 8

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire and rescue

CERTIFICATIONS

- cETLus, ATEX, IECEx, CE, InMetro

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- 120L, 17.5 hrs. runtime

FLOODLIGHT

- 120L, 17.5 hrs. runtime

DUAL-LIGHT

- 240L, 4.5 hrs. runtime

CANDELA

- 7,250

BEAM DISTANCE

- 170 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.0 in (178 mm)
- HANDLE DIAMETER: 1.1 in x 1.5 in (28 mm x 38 mm)
- HEAD DIAMETER: 1.8 in (46 mm)
- WEIGHT: 6.9 oz (196 g)

POWER SOURCE


- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Flashlight
- Removable lanyard
- Instruction manual

FL 1 STANDARD	SPOT	FLOOD	DUAL-LIGHT
	120 LUMENS	120 LUMENS	240 LUMENS
	17h	17h	4h 30min
	170m		
	7250cd		
	2m		
	1m		

Bayco Products, Inc.
640 S. Sanden Blvd.
Wylie, TX 75098

XPP-5422GA




Intertek



ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
CLASS II & III DIV 1 GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T4 Ga
CLASS II ZONE 20 AEx ia IIC T4 Ga
⊕ 1 M1 Ex ia I Ma
⊕ II 1 G Ex ia IIC T4 Ga
⊕ II 1 G Ex ia IIC T135°C Da

Conforms to:
ANSI/UL STD 913, ANSI/UL 60079-0,
ANSI/UL 60079-11 ANSI/ISA 60079-26



Ex ia I Ma
Ex ia IIC T4 Ga
Ex ia IIC T135°C Da
ITS 13 ATEX27837X
ITS21UKEX0264X
IECEx ITS 16.0067X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AA Alkaline

Certified to:
CAN/CSA STD C22.2 No 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25

CERTIFIED

