

3 AAA (included)

XPP-5452G

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

NIGHTSTICK®
Life Depends on Light




Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



Single Body Switch. High-brightness Spotlight, Low-brightness Spotlight



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



Adjustable ratchet tilt head made from an engineered polymer housing

**ATEX
ZONE 0
IECEx**

**CLASS I
DIV 1**

**IPX7
WATER
PROOF**

CERTIFIED



180 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

3 AAA INCLUDED

ITEM NUMBER/UPC

- XPP-5452G, UPC 0 1739880301 4

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, Kosha

CASE MATERIAL

- Engineered Polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 180L, 6 hrs. runtime
- LOW: 90L, 19 hrs. runtime

CANDELA

- HIGH: 2,180
- LOW: 962

BEAM DISTANCE

- HIGH: 93m
- LOW: 62m

DUST/WATER RATING

ANSI IP-67 Dustproof / Waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 2.4 in (61 mm)
- WIDTH: 1.9 in (48 mm)
- DEPTH: 1.8 in (46 mm)
- WEIGHT: 3.5 oz (99 g)

BATTERY

- 3 AAA (Included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp
- 3 AAA batteries
- Elastic non-slip headband
- Rubber hardhat strap
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	180 LUMENS	90 LUMENS
	6h	19h
	93m	62m
	2180cd	962cd
		
		

NIGHTSTICK XPP-5452G

Bayco Products, Inc. 640 S. Sanden Blvd., Wylie, TX 75098






CLASS I DIV 1 GRPS A-D T4
 CLASS II & III GRPS E-G T135°C
 CLASS I ZONE 0 AEx ia IIC T4 Ga
 CLASS I ZONE 0 Ex ia IIC T4 Ga
 Ⓜ II 1 G Ex ia IIC T4 Ga
 Ⓜ II 1 D Ex ia IIC T4 135°C Da

ITS 13 ATEX27854X
 ETL26CA106455615X
 IECEx ITS 17.0002X
 -20°C ≤ Tamb ≤ +40°C
 1.5V/Cell AAA Alkaline
 IP-67

Intertek
 ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

Ex ia IIC T4 Ga
 Ex ia IIC T4 135°C Da

22-AV/4B0-0216X
 SEE INSTRUCTION MANUAL
 VOIR MANUEL

MFG MM-YY

CERTIFIED
    