

3 AAA BATTERIES

XPP-5454GC

INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

NIGHTSTICK
Life Depends on Light



Dual-Light™ spotlight and floodlight at the same time



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



Adjustable ratchet tilt head made from an engineered polymer housing



Dual Body Switches. High/Low Spotlight, High/Low Floodlight, Dual-Light

**DUAL
LIGHT
TECHNOLOGY**

**IP67
DUST/WATER
PROOF**

**CLASS I
DIV 1**

**ATEX
ZONE 0
IECEx**



Includes: Light, batteries, NS-HMC4 mount.



190 LUMENS

1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2023 Bayco Products Inc. Items shown are intended as a visual representation only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

3 AAA BATTERIES

ITEM NUMBER/UPC

- XPP-5454GC, UPC 0 17398 80450 9

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, InMetro, UKCA

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- HIGH: 160L, 5 hrs. runtime
- LOW: 85L, 16 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH: 130L, 5 hrs. runtime
- LOW: 70L, 15 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- HIGH: 190L, 4 hrs. runtime

CANDELA

- HIGH: 2,135
- LOW: 1,100

BEAM DISTANCE

- HIGH: 154m
- LOW: 85m

DUST/WATER RATING

ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 2.1 in (53 mm)
- WIDTH: 2.6 in (66 mm)
- DEPTH: 1.8 in (46 mm)
- WEIGHT: 3.3 oz (97 g)

BATTERY

- AAA

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp
- Elastic Non-Slip Headband
- NS-HMC4 Hardhat Mount
- Alcohol Cleaning Swab
- 3 AAA batteries
- Instruction manual

FL1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	160 LUMENS	85 LUMENS	190 LUMENS
	5h	16h	4h
	154m		
	2135cd		
	2m		
	1m		

NIGHTSTICK

CLASS I DIV 1 GRPS A-D T3
CLASS II & III GRPS E-G T135°C
CLASS I ZONE 0 AEx ia IIC T3 Ga
Ex ia IIC T3 Ga
Ex ia op is IIC T3 Ga
Ex ia op is IIC T3 Ga
Intertek ITS 13 ATEX27928X
ITS21UKE0266X
IECEx ITS 18.0030X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell E92 or EN92
SEE INSTRUCTION MANUAL

XPP-5454GC

Bayco Products, Inc.
640 S. Sanden Blvd.
Wylie, TX 75098



Intertek

ID 5012927
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

UK
CA 0359

CE 2575



US Patent 9,713,217
MFG MM-YY

CERTIFIED

